

TECHNICAL DATA SHEET

RRC2130

Specification






General	
Delivery status battery capacity	30%
Compliance information	IEC 62133 / CE / UL2054 / FCC / Gost / PSE / BSMI / TISI / RCM / EAC / CQC / KC / BIS / UN38.3 / RoHS / REACH
Operating temperature	0°C to 45°C (charge) -20°C to 60°C (discharge)
Storage temperature	-20°C to 60°C max. -20°C to 25°C recommended

Electrical Parameters	
Nominal voltage	7.60V
Nominal capacity	3.88Ah
Initial impedance	<200mΩ @ 1kHz at 20°C
Max. charge current	2.70A
Max. charge voltage	8.70V
Cont. discharge	3.78A
Max. discharge	5.67A
Life expectancy @ 25°C 1.89A Charge/3.78A Discharge	>300 cycles with ≥ 85% of initial capacity

Battery Dimensions	
Length	150.60mm +0.5/-0.5
Width	86.20mm +0.4/-0.4
Thickness	8.35mm +0.25/-0.25
Weight	172g
Contacts	+, +, C, D, T, -, -

Safety Parameters PCM	
Overcharge detection voltage / cell	4.39V
Overcharge release voltage / cell	4.20V
Overdischarge detection voltage / cell	2.75V
Overdischarge release voltage / cell	3.25V
Overcharge detection current	3.10A
Overdischarge detection current	6.00A

Recommended Accessories

Type	Product	P/N	Application
Standard Battery Charger	 RRC-SMB-FPC	110083	40.00W standard battery charger for optimized charging process with external power supply for world-wide use.
Battery Mating Connector	 RRC-MC21-90-10 RRC-MC21-90-20	211268 211278	Mating Connector for standard smart batteries RRC2130, RRC2140. Available for 90° PCB mounting (top and edge).
Power Supply AC/DC	 PS65	210919	External power supply (worldwide use) for embedded battery charger RRC-PMM240 or for mobile devices. Included in RRC-SMB-FPC.
AC Power Cable	 USA/CAN/JPN EU/KOR UK/SGP AUS/NZL	210950 210951 211333 211334	Country specific power cable for PS65.
Car Adapter DC/DC	 RRC-SMB-CAR	110041	90.00W car adapter with USB charging port. Power supplying in cars and trucks for RRC-SMB-FPC, RRC-PMM240 or mobile devices

Germany/Headquarters

RRC power solutions GmbH
Technologiepark 1
66424 Homburg / Saar

Tel.: +49 6841 98090
Fax: +49 6841 9809280
Email: sales@rrc-ps.de
Web: www.rrc-ps.de

USA

RRC power solutions Inc.
18340 Yorba Linda Blvd.,
107-437 Yorba Linda,
CA 92886-4104

Tel.: +1 714 777 3604
Fax: +1 714 777 3658
Email: usa@rrc-ps.com
Web: www.rrc-ps.com

Hong Kong

RRC power solutions Ltd.
S-V,6/F, Valiant Industrial
Centre 2-12 Au Pui Wan Street
Fo Tan, N.T., Hong Kong

Tel.: +852 2376 0106
Fax: +852 2375 0107
Email: hkrrc@rrc-ps.cn
Web: www.rrc-ps.com

China

RRC power solutions Ltd.
Room 1306, C Building,
Tianan International building,
Renmin South Road, Luohu
District, Shenzhen 518021

Tel.: +86 755 8374 1908
Fax: +86 755 8374 1861
Email: hkrrc@rrc-ps.cn
Web: www.rrc-ps.com