

BATTERY CHARGER, 453743-N, NiMH

SPECIFICATIONS	2	3-6	4-8	5-10	6-12	10-20	15-30
Cell-Con part number:	453743-NZ	453743-NA	453743-NB	453743-NC	453743-ND	453743-NE	453743-NK
Input voltage:	90-264VAC						
Line frequency:	47-63Hz						
Max output power:	6.5W	14W	14.7W	14.9W	15.3W	14.4W	15.3W
Min. output voltage for -ΔV detection:	2.5V (min 2 cells x min 1.25V pr. cell)	3.75V (min 3 cells x min 1.25V pr. cell)	5.0V (min 4 cells x min 1.25V pr. cell)	6.2V (min 5 cells x min 1.25V pr. cell)	7.5V (min 6 cells x min 1.25V pr. cell)	12.5V (min 10 cells x min 1.25V pr. cell)	18.75V (min 15 cells x min 1.25V pr. cell)
Max. output voltage for -ΔV detection:	3.4V (max 2 cells x max 1.7V pr. cell)	10.2V (max 6 cells x max 1.7V pr. cell)	13.6V (max 8 cells x max 1.7V pr. cell)	17V (max 10 cells x max 1.7V pr. cell)	20.4V (max 12 cells x max 1.7V pr. cell)	34V (max 20 cells x max 1.7V pr. cell)	51V (max 30 cells x max 1.7V pr. cell)
-ΔV sensitivity mV/cell:	3mV/cell		3mV/cell (approx.)				
SoftStart current:	100mA ±30mA @Vbat <2.5V	100mA ±30mA @Vbat <3.75V	60mA ±20mA @Vbat <5.0V	60mA ±20mA @Vbat <6.25V	50mA ±20mA @Vbat <7.5V	40mA ±20mA @Vbat <12.9V	30mA ±20mA @Vbat <18.5V
Fast charge current:	1.3A ±100mA	1.3A ±100mA	1.0A ±100mA	0.8A ±100mA	0.7A ±100mA	400mA ±50mA	300mA ±50mA
Top off charge:	160mA ±30mA	160mA ±30mA	130mA ±30mA	110mA ±30mA	100mA ±30mA	65mA ±20mA	55mA ±20mA
Trickle charge current:	30mA ±15mA					25mA ±10mA	
Efficiency at 100% load:	0.7	0.76	0.78	0.8	0.81	0.84	
Average efficency:	>62%	>72%	>74%	>76%	>77%	>80%	
No load consumption:	0.5W	0.6W	0.6W	0.65W	0.7W	0.5W	0.75W
-ΔV mask start timer:	3 min, no -ΔV detection in this period.						
SoftStart timer:	30 minutes						
Top-off timer:	1 hour						
Safety timer - The charger switch to trickle charge if no ΔV is detected before the safety timer has run out:	5 hours						
Switch frequency:	56kHz						
Temperature range:	-20 to +40°C (these values are only for the charger, not for the batteries).						
Charge control:	-ΔV principle. Fast charging stops when the voltage has dropped 3mV/cell below its maximum recorded level.						
Voltage changes during charging:	-ΔV detection is disabled if the voltage changes quickly. This to avoid false -ΔV if an external load kicks in during charging.						
Leakage current from battery with mains switch off:	<300µA at nominal battery voltage (<0.22 Ah/month)						
Fuses:	Fuse at input. Mosfet switch at the output protects the unit against wrong polarity.						
Insulation class:	Class II						
Electrical safety:	**Medical**: EN 60601-1 / **Home Health Care:** EN 60601-1-11 / **Battery Charger:** EN 60335-2-29						
EMC-standards:	EN 55014-1 and –2, EN 61000-6-3, EN 61000-6-1, EN 60601-1-2						
Insulation voltage (primary-secondary):	4000V AC/5700V DC						
Input terminals:	2-pins IEC 320 connector for exchangeable mains plug (EU, US, UK and AUS) or mains cord with C7 connector.						
Output terminals:	Cord with/without plug. Exchangeable plugs available.						
LED-indication:	SoftStart/Fast charge: Yellow Top off charge: Flashing Yellow Trickle charge: Green Battery not connected: Flashing Green (1s/1s)						
Protection:	Protected against reversed polarity. Error indication: Red (2 blinks). Short circuit proof. Error indication: Red (3 blinks). Low battery voltage (SoftStart timer). Error indication: Red (4 blinks). No charge (or charge terminated) if connecting wrong battery pack with higher voltage. Indication: LED is OFF.						
Thermal control (Optional, requires battery with NTC):	+dT/dt principle. Fast charging stops when the temperature increment is over 0.5°C/min. Battery temperature is too low (<0°C). Wait mode. Indication: Yellow with 1 red blink. Battery temperature is too high (>40°C). Wait mode. Indication: Yellow with 2 red blinks. High temperature (>60°C). Error Indication: Red (5 blinks). NTC missing or shorted. Error Indication: Red (6 blinks).						
Resetting:	A new charging cycle starts by reconnecting a battery at the output, or by disconnecting and connecting the main voltage.						
IP-grade:	IP 41						
Dimensions:	108.5×49×29.3mm						
Weight:	150g						
Other:	Possible options on request: Charger parameters programmable with “Configurator tool”. Constant current charge (no battery management). 0dV detection for EoC. DoE compliance.						

CELL-CON
Battery & Charger Solutions

www.cell-con.com
2 Enterprise Lane, Bedford, PA 15522 | P: 800.771.7139 | sales@cell-con.com